

CR Series - Vacuum & Gas Flushing Impulse Sealer for Clean Room Facilities



The CR-600 vacuum sealing machine meets all clean room requirements! This impulse sealer is manufactured inside a clean booth and shipped after inspection. It is hermetically sealed and shipped only after the measured result is verified to be class 1000 or less. Shipment inspection points include using a device to measure cleanliness during sealer operation. The CR-600 impulse sealer comes standard with the ONPUL temperature-control system. This impulse sealer also comes standard with a touch-screen LCD panel for optimal usage. A HEPA filter is an available option, to minimize particles in the exhaust air. MAIN FEATURES:

- Temperature control [ONPUL](#) system standard equipment
- Touch panel operation for easy setting
- New table mechanism for easy height adjustment
- Flange for the integrated exhaust duct standard equipped
- Optional HEPA filter available to minimize particals in exhaust air

CLEAN & HIGH TECHNOLOGY Inside installed fan: 3 fans inside the machine body create airflow downward, so that all the particles inside the body cover and heating area are concentrated to the exhaust duct. Inside installed filter: Air filter for a vacuum pump is installed inside the machine body to decrease the unevenness of the body and make it compact. Exhaust fan: All the particles generated inside the machine body through the sealing operation are concentrated to the exhaust fan to be exhausted outside. Flange for the integrated exhaust duct: Set a duct to the flange so that all the particles concentrated through the exhaust fan are exhausted to the outside of a cleanroom. Easy touch panel display: Set values are displayed on touch panel display for easy understanding.

- [How to maintain CR-600 Series](#)
- [How to troubleshoot CR-600 Series](#)

Model	Voltage	Power Consumption	Sealing Dimensions - W X L	Machine Dimensions - W X D X H	Weight	Voltage	Power Consumption	Sealing Dimensions - W X L
CR-600	220 V	3000 W	10 X 600 mm (0.39" X 23.6")	730 X 855 X 1110 mm (28.7" X 33.7")	130Kg (289Lbs)			

---

CR-600-10D	220 V	3000 W	10 X 600 mm (0.39" X 23.6")	X 43.7") (Table included) 730 X 855 X 1110 mm (28.7" X 33.7" X 43.7") (Table included)	130Kg (289Lbs)
------------	-------	--------	-----------------------------------	--	-------------------